



**BATA INDUSTRIALS**  
THE SAFETY SHOE

# BATA ENDURO COLLECTION

SERIOUSLY SAFE 



|                          |                                                                        |
|--------------------------|------------------------------------------------------------------------|
| Article name             | ACT220 ESD S3                                                          |
| Article number           | N2SM0PE2210 (W); N2SM0PE2211 (XW)                                      |
| Upper material           | Full grain leather                                                     |
| Lining material          | Polyester Mesh black with Bata Cool Comfort® + Lining and Odor Control |
| Insole                   | Refer: Anti perforation insert                                         |
| Inlay sole               | 85% GRS POLIYOU® foam black                                            |
| Mid sole                 | Bio-based PU black                                                     |
| Outsole                  | Bio-based PU black   Ladder Grip                                       |
| Safety toecap            | Aluminum                                                               |
| Anti perforation insert  | Steel-penetration resistance 1100 N                                    |
| Outer toecap (Scuff Cap) | None                                                                   |
| Sizes                    | 35-48 / UK 2-13                                                        |
| Widths                   | W, XW                                                                  |
| Closure                  | Laces                                                                  |

## TECHNICAL CHARACTERISTICS



**Upper**  
Full grain leather



**Lining**  
Polyester Mesh black with Bata Cool Comfort® + Lining and Odor Control



**Model**  
Mid cut S3



**Colour**  
Black



**Electrostatic Properties**  
ESD



**Outsole**  
Bio-based PU black | Ladder Grip



**Safety toecap**  
Aluminum



**Anti perforation insert**  
Steel-penetration resistance 1100 N



**Outer toecap**  
None



**Size range**  
W 35-48, XW 38-48 /  
UK W 2-13, XW 5-13



**Widths**  
W, XW



**Closure**  
Laces

EN ISO 20345:2022 S3 HI CI SR LG FO



Europaplein 1, 5684 ZC Best, The Netherlands | P.O. Box 10050, 5680 BD Best, The Netherlands  
T +31 (0)499 362 911 | F +31 (0)499 362 948 | nl.info@bata.com | bataindustrials.com

**SERIOUSLY.**