

ACT260 W



BASIC INFORMATION

Article no.	P2LMKPE2210 (W)
Safety category	S3S
Standard	EN ISO 20345:2022 + A1 2024 S3S CI FO LG SC SR
DGUV	No
Model	Mid cut

SIZE RANGE

Width	FR	UK
W	35-48	2-13

DESCRIPTION

The Chelsea Boot is easy to slip on with elastic sides, offering protection with an aluminum toe and FlexGuard® non-metallic insert. Walkline® 3.0 technology and supportive systems ensure comfort, making it perfect for work and leisure.

RECOMMENDED FOR

Construction
Light Industry
Logistics

MATERIAL PROPERTIES

Safety toecap	Aluminum
Perforation-resistant insert	FlexGuard® non-metallic insert
Upper	Oiled pull up leather
Midsole	Bio-based PU
Outsole	Bio-based PU
Inlay sole	Premium Fit 82% GRS recycled POLIYOU®
Insole	FlexGuard® non-metallic insert
Lining	Polyester with Odor Control
Closure	Slip on
Shank	2 density shank

SAFETY FEATURES

A	- Antistatic
CI	- Cold Insulation
E	- Energy absorption of seat region
F0	- Fuel and oil resistant outsole
LG	- Outsole with Ladder Grip
PS	- Non-metal insert resistant to nails down to ø 3.0 mm
SC	- PU abrasion resistant scuff cap
SR	- Slip resistance (2022 standard)
WPA	- Water penetration and absorption resistant upper

FEATURES AND TECHNOLOGIES

Dual density sole
Bata Cool Comfort® + Lining and Odor Control

CERTIFIED WITH INLAY SOLES

None

CERTIFICATIONS



PARTNERS

POLIYOU
POWERED BY KUN HUANG

PACKAGING

35-48

Gross weight (g)	1.6
Net weight (g)	1.4
Unit package LxHxW (mm)	358x259x126
Units per carton	5
Carton LxHxW (mm)	655x278x372
Units per container 20 foot	2300-2500
Units per container 40 foot	5200-5400
Units per container 40 foot HQ	6000-6300