

OVERLAND ULTRA SAND



BASIC INFORMATION

Article no.	706-37090
Safety category	S3S
Standard	EN ISO 20345:2022+A1:2024 S3S HI CI LG HRO SR FO
DGUV	No
Model	High cut
Country of origin	CN

SIZE RANGE

Width	FR	UK
XW	36-49	3-14

DESCRIPTION

High-cut zip sided safety shoe featuring a sand-colored nubuck leather upper, combined with a Michelin-designed rubber outsole.

RECOMMENDED FOR

Construction
Heavy Industry

MATERIAL PROPERTIES

Safety toecap	Composite
Perforation-resistant insert	FlexGuard® non-metallic insert
Upper	Nubuck leather
Midsole	PU
Outsole	Michelin, rubber
Inlay sole	PU suedtec, preshaped PU footbed with memory foam layer
Insole	FlexGuard® non-metallic insert
Lining	Polyester with None
Closure	Laces and zipper, Polyester,
Scuff cap	TPU
Shank	None

SAFETY FEATURES

A	- Antistatic
CI	- Cold insulation
E	- Energy absorption of seat region
FO	- Fuel and oil resistant outsole
HI	- Heat insulation
HR0	- Heat resistant outsole
LG	- Outsole with Ladder Grip
PS	- Non-metal insert resistant to nails down to ø 3.0 mm
SR	- Slip resistance
WPA	- Water penetration and absorption resistant upper

FEATURES AND TECHNOLOGIES

Bellows tongue
Heel grip
Dual density sole
Bata Cool Comfort®
Metal-free

CERTIFIED WITH INLAY SOLES

None

CERTIFICATIONS



PARTNERS

SOLES
BY



PACKAGING

	36-39	40-43	44-49
Gross weight (pair) (kg)	2.10		
Net weight (pair) (kg)	1.80		
Unit package L×W×H (mm)	310×290×120	330×310×125	380×335×135
Units per carton	5	5	5
Carton L×W×H (mm)	620×310×330	645×330×350	695×355×400
Units per container 20 foot	2000-2300		
Units per container 40 foot	4800-5200		
Units per container 40 foot HQ	5800-6200		