BATA INDUSTRIALS

HELIX

OVERLAND ULTRA BLACK







BASIC INFORMATION

Article no.	706-67089
Safety category	S3S
Standard	EN ISO 20345:2022+A1:2024 S3S HI CI LG HRO SR FO SC
DGUV	No
Model	High cut
Country of origin	CN

SIZE RANGE

Width	FR	UK
XW	36–49	3–14

DESCRIPTION

High-cut zip sided safety shoe featuring a black nubuck leather upper, combined with a Michelin-designed rubber outsole.

RECOMMENDED FOR

Construction
Heavy Industry

Work safe. Live great.

MATERIAL PROPERTIES

Safety toecap	Composite
Perforation-resistant insert	FlexGuard® non-metallic insert
Upper	Nubuck leather
Midsole	PU
Outsole	Michelin, rubber
Inlay sole	PU suedtec, preshaped PU footbed with memory foam layer
Insole	FlexGuard® non-metallic insert
Lining	Polyester
Closure	Laces and zipper
Scuff cap	TPU
Shank	None

SAFETY FEATURES

A – Antistatic
CI – Cold insulation
E – Energy absorption of seat region
FO – Fuel and oil resistant outsole
HI – Heat insulation
HRO – Heat resistant outsole
LG – Outsole with Ladder Grip
PS – Non-metal insert resistant to nails down to ø 3.0 mm
SC – Abrasion resistant scuff cap
SR – Slip resistance
WPA – Water penetration and absorption resistant upper

FEATURES AND TECHNOLOGIES

Bellows tongue
Heel grip
Dual density sole
Bata Cool Comfort®
Metal-free

CERTIFIED WITH INLAY SOLES

None

CERTIFICATIONS

MEMBER OF LEATHER WORKING GROUP

PARTNERS

SOLES BY MICHELIN

PACKAGING

	36–39	40–43	44–49
Gross weight (pair) (kg)		2.12	
Net weight (pair) (kg)		1.82	
Unit package L×W×H (mm)	310×290×120	330×310×125	380×335×135
Units per carton	5	5	5
Carton L×W×H (mm)	620×310×330	645×330×350	695×355×400
Units per container 20 foot		2000–2300	
Units per container 40 foot		4800–5200	
Units per container 40 foot HQ		5800–6200	