BATA INDUSTRIALS

HELIX

RANGER BOA ULTRA BLACK





BASIC INFORMATION

Article no.	706-67088
Safety category	S3S
Standard	EN ISO 20345:2022+A1:2024 S3S HI CI LG HRO SR FO SC
DGUV	No
Model	High cut
Country of origin	CN

SIZE RANGE

Width	FR	UK
XW	36–49	3–14

DESCRIPTION

High-cut safety shoe with a BOA® Fit System for quick, precise adjustment and a secure fit. Offered in black full grain leather, with a Michelin rubber outsole for dependable grip and all-day comfort.

RECOMMENDED FOR

Construction
Heavy Industry

Work safe. Live great.

MATERIAL PROPERTIES

Safety toecap	Composite
Perforation-resistant insert	FlexGuard® non-metallic insert
Upper	Full grain leather
Midsole	PU
Outsole	Michelin, rubber
Inlay sole	PU suedtec, preshaped PU footbed with memory foam layer
Insole	FlexGuard® non-metallic insert
Lining	Polyester
Closure	BOA® Fit System
Scuff cap	TPU
Shank	None

SAFETY FEATURES

A – Antistatic
CI – Cold insulation
E – Energy absorption of seat region
FO – Fuel and oil resistant outsole
HI – Heat insulation
HRO – Heat resistant outsole
LG – Outsole with Ladder Grip
PS – Non-metal insert resistant to nails down to ø 3.0 mm
SC – Abrasion resistant scuff cap
SR – Slip resistance
WPA – Water penetration and absorption resistant upper

FEATURES AND TECHNOLOGIES

Bellows tongue
Heel grip
Dual density sole
Bata Cool Comfort®
Detection-friendly

CERTIFIED WITH INLAY SOLES

None

CERTIFICATIONS

PARTNERS

PACKAGING

	36–39	40–43	44–49
Gross weight (pair) (kg)		2.15	
Net weight (pair) (kg)		1.85	
Unit package L×W×H (mm)	310×290×120	330×310×125	380×335×135
Units per carton	5	5	5
Carton L×W×H (mm)	620×310×330	645×330×350	695×350×400
Units per container 20 foot		2000–2300	
Units per container 40 foot		4800–5200	
Units per container 40 foot HQ		5800–6200	